

WWW.PAITEC.COM • 877-295-SEAL (7325)

ADJUSTABLE SPEED

Adjustable speed allows operator to work at a comfortable speed and auiet environment.

FOUR-ROLLER SEALING UNIT

MX11000

A second pair of sealing rollers enables enhanced sealing quality at higher speed.

HEAVY DUT CYCLE

Enhanced parts and life cycle on rollers allow MX11000 to operate up to 200,000 sheets per month.

REVERSE FRICTION ROLL

Unique RFR system, automatically detects, singulates, and corrects doubles without any operator intervention for increased productivity.

| | FORM SIZE | Depth – Up to 14"/ Width – Up to 9" |
|-------|-------------------|--|
| Ions | INPUT TRAY | Up to 700 Pressure Seal Forms |
| | SPEED | Up to 11,000 Sheet/Hour (Adjustable Speed) |
| | FOLD SETTING | Quick Set Manual |
| | PAPER WEIGHT | 20 -28 Lb. Bond |
| | INFEED TYPE | Reverse Friction Roller With Cooling Fan |
| | MANUAL FEEDER | Process Single or Damaged Forms |
| | FOLD TYPE | Z, EZ, C, EC, V, & Double Parallel |
| | BATCH COUNTER | Auto Start for Job Separation |
| | DOUBLE DETECTION | Automatically Detects Double Feeds |
| licat | JAM FREE | Reverses the Rollers and Clears Any Jam |
| | OUTPUT CAPACITY | Auto-Extending Conveyer Stacker (350 sheets) Vertical/Sequential Stacker (350 sheets) |
| Deci | PRINTER INTERFACE | Optional Inline Kit To Select Printers |
| | DUTY CYCLE | 200,000 Sheets Per Month |
| | WEIGHT | 130 Lb. |
| 5 | SIZE | 17 x 24 x 15 In. (W x L x H)/Without Conveyor |

Note: All care has been taken in the preparation of the specifications and description. As they are subject to change, they should not be part of any contract.

WWW.PAITEC.COM • 877-295-SEAL (7325)

LARGE INFEED CAPACIT

The easy-to-load, auto-lift infeed holds up to 700 sheets for saving time throughout processing.



R

paitec