



WWW.PAITEC.COM • 877-295-SEAL (7325)

ADJUSTABLE SPEED

Adjustable speed allows operator to work at a comfortable speed and auiet environment.

FOUR-ROLLER SEALING UNIT

MX9000

A second pair of sealing rollers enables enhanced sealing quality at higher speed.

HEAVY DUT CYCLE

Enhanced parts and life cycle on rollers allow MX9000 to operate up to 300,000 sheets per month.

REVERSE FRICTION ROLL

Unique RFR system, automatically detects, singulates, and corrects doubles without any operator intervention for increased productivity.

	FORM SIZE	Depth – Up to 14"/ Width – Up to 9"
Ions	INPUT TRAY	Up to 700 Pressure Seal Forms
	SPEED	Up to 9,000 Sheet/Hour (Adjustable Speed)
	FOLD SETTING	Quick Set Manual
	PAPER WEIGHT	20 -28 Lb. Bond
	INFEED TYPE	Reverse Friction Roller With Cooling Fan
	MANUAL FEEDER	Process Single or Damaged Forms
	FOLD TYPE	Z, EZ, C, EC, V, & Double Parallel
	BATCH COUNTER	Auto Start for Job Separation
	DOUBLE DETECTION	Automatically Detects Double Feeds
licat	JAM FREE	Reverses the Rollers and Clears Any Jam
	OUTPUT CAPACITY	Auto-Extending Conveyer Stacker (650 sheets) Vertical/Sequential Stacker (650 sheets)
Deci	PRINTER INTERFACE	Optional Inline Kit To Select Printers
	DUTY CYCLE	300,000 Sheets Per Month
	WEIGHT	130 Lb.
5	SIZE	17 x 24 x 15 In. (W x L x H)/Without Conveyor

Note: All care has been taken in the preparation of the specifications and description. As they are subject to change, they should not be part of any contract.

WWW.PAITEC.COM • 877-295-SEAL (7325)

LARGE INFEED

The easy-to-load, auto-lift infeed holds up to 700 sheets for saving time throughout processing.



R



